TSLC
THE SMART LIGHTING COMPANY

Date: .....
Type: .....
Project: .....
Firm: .....



HB50C RGBW

HIGH POWER LINEAR LED LIGHTBAR

High Power | High Intensity
20w/ft | 984lm/ft | DMX







Exterior: Graze | Wall Washing | Accent | Flood Lighting

The Smart Lighting Company HB50C RGBW Series is a robust color changing LED linear architectural fixture designed to outperform more expensive brands. Delivering 20 watts per foot, this fixture is ideal for vibrant high-intensity wall grazing, washing, accent, and flood illumination. Utilizing high-quality Nichia bin-sorted LEDs, the HB50C ensures even, superior illumination that architects and lighting designers seek. This fixture is geared for powerful illumination over 60 feet, making it suitable for a variety of outdoor applications. It comes with a selection of precise optics, allowing you to achieve the exact lighting effect you desire with less energy use. The HB50C RGBW is self-contained with an integral universal 100/277VAC power supply and self-addressing features, ensuring a seamless installation process. With DMX control, multiple customization options for fixture length, optics, and finishes, and a Plug and Play system for easy setup, the HB50C is a versatile choice. Additional mounting options and accessories, like powder-coated housing with integral glare shields, make it ideal for projects requiring intense, precise lighting effects.

DIMMABLE IP66 LM80 TESTED LEDS CSA c UL us LISTED NICHIA

1731 Kaiser Ave. Irvine, CA 92614 | sales@thesmartlightingcompany.com | 949.346.3456 | thesmartlightingcompany.com
© 2021 The Smart Lighting Company. All rights reserved. Speci ications subject to change without notice. Rev. 03/23

technology by LEDpower

TSLC THE SMART LIGHTING COMPANY

HB50C

HIGH POWER LINEAR LED LIGHTBAR

SPECIFICATIONS

Date: .....
Type: .....
Project: .....
Firm: .....

PERFORMANCE

Output
20w/ft | 984lm/ft

Color Temperatures
RGBW

Beam Angles
15°, 20°, 30°, 45°, 60°, 75°, 90°, 120°, 15°x35°, 18°x58°, & 30°x60°

LEDs per Foot
16 (4R, 4G, 4B, 4W) LEDs/ft

LED's
Nichia bin-sorted

Color Consistency
2 SCDM

ELECTRICAL

Input Voltage
Universal 100/277VAC

Driver
Integrated Driver

Control
DMX

Resolution
Per 12" or per fixture

Heat dissipation
Full thermal management system

Connection
Quick connect plug and play system (power and signal in one cable)

Projected Lumen Maintenance
>90,000 hours

PHYSICAL

Fixture Length Options
12", 24", 36", 48"

Max Run Length
110ft@277vac, 48ft@120vac

Housing
Extruded gray aluminum

Lens
Tempered Glass

Fixture Finish (Standard)
Anodized aluminum

Powder Coated Finish (Optional)
Black, Bronze, White, CU

Standard Mounting
Adjustable brackets

Optional Mounting
Powder-coated housing|extended arms or ground post stakes

Operating Temperature
-40°F to 122°F, (-40°C to +50°C)

ENVIRONMENT AND WARRANTY

IP Rating
IP66

Environment
Dry, Damp or Wet locations
0-100% non-condensing humidity

Certifications
UL, cUL

Warranty
5 year limited warranty

1731 Kaiser Ave. Irvine, CA 92614 | sales@thesmartlightingcompany.com | 949.346.3456 | thesmartlightingcompany.com
© 2021 The Smart Lighting Company. All rights reserved. Specifications subject to change without notice. Rev. 03/23

HB50C

HIGH POWER LINEAR LED LIGHTBAR


SPECIFICATIONS

Date: .....
Type: .....
Project: .....
Firm: .....


PHYSICAL

OPTICS


15°x 15°




20°x 20°




30°x 30°




45°x 45°




120°x 120°




10°x 60°



15°x 35°



30°x 60°




COLOR TEMPERATURES




DIMENSIONS AND DATA

Model Number	Volt-age	View Angle	Watts/ Fixture	Lumens/ Fixture	LEDs/ Fixture	Extrusion Length	Total Length
HB50C-12”-RGBW-XXD-AC-DX	100-277VAC	15°, 20°, 30°, 45° 60°, 75°, 90°,120°, 15°x35°, 18°x58°, 30°x60°	20	984lm	4R, 4G, 4B, 4W	12.17” (309mm)	12.64” (321mm)
HB50C-24”-RGBW-XXD-AC-DX			40	1968lm	8R, 8G, 8B, 8W	23.90” (607mm)	24.37” (619mm)
HB50C-36”-RGBW-XXD-AC-DX			60	2952lm	12R, 12G, 12B, 12W	35.63” (905mm)	36.1” (917mm)
HB50C-48”-RGBW-XXD-AC-DX			80	3936lm	16R, 16G, 16B, 16W	47.56” (1208mm)	48” (1220mm)

PROFILE





1731 Kaiser Ave. Irvine, CA 92614 | sales@thesmartlightingcompany.com | 949.346.3456 | thesmartlightingcompany.com
© 2021 The Smart Lighting Company. All rights reserved. Specifications subject to change without notice. Rev. 03/23

technology by LEDpower™ TSLC THE SMART LIGHTING COMPANY

HB50C

HIGH POWER LINEAR
LED LIGHTBAR

ORDER FORM

Date: .....
Type: .....
Project: .....
Firm: .....

CREATE YOUR FIXTURE

Ex. HB50C-48-RGBW65-3060-AC-DM

MODEL

HB50C

LENGTH

12”	12 inches
24”	24 inches
36”	36 inches
48”	48 inches

COLOR

RGBW

Select the W - 65k is standard

27k	2700k
30k	3000k
35k	3500k
41k	4100k
50k	5000k
65k	6500k
A	Amber

OPTICS

15	15°x15°	1535	15°x35°
20	20°x20°	1858	18°x58°
30	30°x30°	3060	30°x60°
45	45°x45°		
60	60°x60°		
75	75°x75°		
90	90°x90°		
120	120°x120°		

VOLTAGE

AC	100-277vac

CONTROL

DM	Addressable /12"
DS	Addressable/fixture

SELECT CONNECTION

Wire Lead

QTY	POWER/SIGNAL	
	HB50-5P-72”-W/L	72” (6ft) Wire Lead
	HB50-5P-xx”- W/L	xx” (CU) Wire Lead (custom length – consult factory)

** 1 wire lead and end cap required for each run.*

End Cap

QTY		
	HB50-5P-END CAP	End cap

Jumper Cable

QTY	POWER/SIGNAL	
	HB50-5P-12”-J	12” (1ft) Jumper Cable
	HB50-5P-72”-J	72” (6ft) Jumper Cable
	HB50-5P-xx”-J	xx” (CU) Jumper Cable (custom length – consult factory)

ADDITIONAL OPTIONS

Optional Powder Coated Finish

QTY	Powder coated finishes available for additional cost	
	BK	Black
	BZ	Bronze
	WH	White
	CU	Custom

** Fixture housing is anodized aluminum standard*

DMX Controller

QTY		
	NIC-DMX-STICK-DE3	DMX controller

Surge Protection

QTY		
	LSP4-UNV	120/277v surge protector

Junction Boxes

QTY		
	AC8A-3WB1-M	Power and signal splitter
	AC8A-3WB2-M	AC Power amplifier for long run lengths
	AC8A-3WB3-M	Power and Wire lead signal splitter

** Used in place of wire leads to separate power and signal*

1731 Kaiser Ave. Irvine, CA 92614 | sales@thesmartlightingcompany.com | 949.346.3456 | thesmartlightingcompany.com
© 2021 The Smart Lighting Company. All rights reserved. Specifications subject to change without notice. Rev. 11/21

POWER/SIGNAL

DISTRIBUTION BOXES

Used at the beginning of the run – All HB50 Series


METAL JUNCTION BOX – POWER AND SIGNAL SPLITTER WITHOUT INPUT WIRES

JUNCTION BOX
AC8A-3WB1-M

INPUT
1/2" hole for conduit fitting for AC power
1/2" hole for conduit fitting for Signal

OUTPUT
72" Cable w 5P Female 5A Connector

For All HB50 Series



* Maximum current 8Amp


METAL JUNCTION BOX – POWER AND SIGNAL SPLITTER WITH INPUT WIRES

JUNCTION BOX
AC8A-3WB3-M

INPUT
10ft PVC 2C Cable for signal
10ft PVC 3C Cable for AC

OUTPUT
72" Cable w 5P Female 5A Connector

For All HB50 Series



*Maximum current 8Amp

© 2021 The Smart Lighting Company. All rights reserved. Specifications subject to change without notice. Rev. 2/23

POWER/SIGNAL

DISTRIBUTION BOXES

Used in the middle of the run – All HB50 Series


METAL JUNCTION BOX–AC POWER AND SIGNAL FOR LONG RUN LENGTHS FOR AC AND SIGNAL WIRE CONNECTION

JUNCTION BOX
AC-2WB2-M

INPUT
12” PVC Cable w/ 5P Male 5A Connector

OUTPUT
12” PVC Cable w/ 5P Female 5A Connector

For All HB Series




METAL JUNCTION BOX–AC POWER AMPLIFIER FOR LONG RUN LENGTHS

JUNCTION BOX
AC8A-3WB2-M

INPUT
12” PVC Cable w/ 5P Male 5A Connector

OUTPUT
12” PVC Cable w/ 5P Female 5A Connector

For All HB50 Series



* Maximum current 8Amp

© 2021 The Smart Lighting Company. All rights reserved. Specifications subject to change without notice. Rev. 2/23

HB50 SERIES


WIRING OPTIONS

Date: .....
Type: .....
Project: .....
Firm: .....


WIRE LEAD

DESCRIPTION
5 pin Power/Signal

PART NUMBER
HB50-5P-xx" 16W/L




Female PVC Cable 16 awg 5 pin




JUMPER CABLE


DESCRIPTION
5 pin Power/Signal

PART NUMBER
HB50-5P-xx" 16J



Female PVC Cable 16 awg 5 pin Male





1731 Kaiser Ave. Irvine, CA 92614 | sales@thesmartlightingcompany.com | 949.346.3456 | thesmartlightingcompany.com
© 2021 The Smart Lighting Company. All rights reserved. Specifications subject to change without notice. Rev. 03/23

HB50 SERIES

ORDER FORM


Date: .....
Type: .....
Project: .....
Firm: .....


MOUNTING OPTIONS

Housing and Extended Arms


HB50EXT-XXL-XXF-XXA (L=Length, F=Finish, A= Extended arm length)

QTY	Housing	(L) Housing Length	(F) Finish	(A) Extended Arm Length
	HB50EXT-	12″	BK - Black	6″
		24″	BZ- Bronze	12″
		36″	WH - White	18″
		48″	SI - Silver	24″
			CU - Custom	36″
				GPA (Ground Post Arm)









** Standard fixture housing is anodized aluminum. Powder coating is available from factory in Black, Bronze, Silver, White, or custom.*
** There is a minimum quantity for powder coating or a surcharge will be added. Custom colors available upon request and will require a cost adder.*
** 1ft & 2ft extrusions require one ground post stake (HBEXP-GPS). 3ft & 4ft extrusions require two ground post stakes (HBEXP-GPS).*

1731 Kaiser Ave. Irvine, CA 92614 | sales@thesmartlightingcompany.com | 949.346.3456 | thesmartlightingcompany.com
© 2021 The Smart Lighting Company. All rights reserved. Specifications subject to change without notice. Rev. 11/21

HB50 SERIES

ORDER FORM

Date: .....
Type: .....
Project: .....
Firm: .....

Ground Posts Stakes


QTY


Select when using GPA above (1 per fixture for 12” & 24” housing and 2 for 36” & 48” housing)


HBEXT-GPS Ground post mount

1ft & 2ft extrusions require one HBEXT-GPS. 3ft & 4ft extrusions require two HBEXT-GPS.









* 12" & 24" extrusions require one HBEXP-GPS
* 36" & 48" extrusions require two HBEXP-GPS

1731 Kaiser Ave. Irvine, CA 92614 | sales@thesmartlightingcompany.com | 949.346.3456 | thesmartlightingcompany.com
© 2021 The Smart Lighting Company. All rights reserved. Specifications subject to change without notice. Rev. 11/21

HB50 SERIES

GLARE PROTECTION


Date: .....
Type: .....
Project: .....
Firm: .....


LOUVERS


Glare Protection


Standard louvers are in Black. Louvers are also available in Bronze, White, or custom.

QTY	Housing	Standard Inch	LEDs/unit	LEDs/Pitch	Louver Length	Total Length	(F) Finish
	HB50-12"LOUVER	12"	6	42.5 mm/1.71 in	309 mm/12.2 in	321 mm/12.6 in	BK - Black
	HB50-24"LOUVER	24"	12	42.5 mm/1.71 in	607 mm/23.9 in	619 mm/24.4 in	BZ- Bronze
	HB50-36"LOUVER	36"	18	42.5 mm/1.71 in	905 mm/35.6 in	917 mm/36.1 in	WH - White
	HB50-48"LOUVER	48"	24	42.5 mm/1.71 in	1208 mm/47.6 in	1220 mm/48 in	SI - Silver
							CU - Custom









1731 Kaiser Ave. Irvine, CA 92614 | sales@thesmartlightingcompany.com | 949.346.3456 | thesmartlightingcompany.com
© 2021 The Smart Lighting Company. All rights reserved. Specifications subject to change without notice. Rev. 11/21

HB50 SERIES


MOUNTING BRACKETS


Date: .....
Type: .....
Project: .....
Firm: .....


INTEGRATED ADJUSTABLE BRACKETS

DESCRIPTION
HB50 Adjustable Bracket

PART NUMBER
AL-HB50 ADJ.Bracket











1731 Kaiser Ave. Irvine, CA 92614 | sales@thesmartlightingcompany.com | 949.346.3456 | thesmartlightingcompany.com
© 2021 The Smart Lighting Company. All rights reserved. Specifications subject to change without notice. Rev. 03/23

Date: .....
Type: .....
Project: .....
Firm: .....

SURGE PROTECTION DEVICE

SURGE PROTECTION

DESCRIPTION
Surge Protection Device

PART NUMBER
AL-LSP-UNV

The use of a surge protection device is necessary to maintain your warranty. Specifications are subject to change without notice.


SPECIFICATIONS

Input Voltage	120-277V (+/- 5%)		
Frequency	50Hz-60Hz		
Maximum Continuous Voltage	320V		
Maximum Discharge Current	L-N 20kA; L-G, N-G 10kA (8/20Qs standard wave)		
Nominal Discharge Current	5kA		
Measured Limiting Voltage (VpK)	L-N	L-G	N-G
	1200	1320	1320
Max Case Temperature	85°C		

PULSE RATING (8 X 20 SEC)		
Surge Level	# of Strikes	
	L-N	L-G, N-G
10,000A	*2	1
6,500A	4	2
5,000A	30	15
2,000A	200	100
700A	20000	1000


**1 strike at 20,000A*

MECHANICAL DIMENSIONS : IN (MM)





WIRING DIAGRAM



1731 Kaiser Ave. Irvine, CA 92614 | sales@thesmartlightingcompany.com | 949.346.3456 | thesmartlightingcompany.com
© 2021 The Smart Lighting Company. All rights reserved. Specifications subject to change without notice. Rev. 03/23