



Motorized Retractable Landscape Lighting

**Rises at
sunset.**
**Retracts at
sunrise.**

- Automatic astronomical time clock or dusk-to-dawn operation based on controller.
- Sleek low-profile housing when retracted.
- IP66 weatherproof.
- Operates on 12 VAC landscape transformer.
- UL Listed
- 3 or 5-year warranty options

WEB www.thesmartlightingcompany.com
EMAIL sales@thesmartlightingcompany.com



EL75DR / EL70DR Series · Retractable Pathway Bollard

PATHWAY & AREA LIGHTING



EL75DR

360° Illumination

AC12V, 5W / 8W
Diameter: 3"
Raised Height: 6" / 12" / 24"
Frosted lens for soft illumination



EL70DR NEW

360° Illumination

AC12V, 5W / 8W
Dimensions: 2.8" x 2.8"
Raised Height: 6" / 12" / 24"
Frosted lens for soft illumination



EL70DD/S

Double / Single-Sided Illumination

AC12V, 2.5W / 5W
Dimensions: 2.8" x 2.8"
Raised Height: 6" / 12" / 24"
Beam Angles: 30°, 30x60°, 60°, 90°



EL70DS-LW NEW

Long Range Wide Beam

AC12V, 2.5W / 5W
Dimensions: 2.8" x 2.8"
Raised Height: 6" / 12" / 24"



EL70DS-LN NEW

Long Range Narrow Beam

AC12V, 2.5W / 5W
Dimensions: 2.8" x 2.8"
Raised Height: 6" / 12" / 24"


WALLWASH LIGHTING



EL70U

Adjustable Up-Light

AC12V, 5W / 8W
Adjustable Projection Angle: 0–45°
Dimensions: 2.8" x 2.8"
Raised Height: 6" / 12" / 24"
Beam Angles: 30° / 30x60° / 60° / 90°



EL90U

120° Wide Beam Illumination

AC12V, 12W
Dimensions: 1.6" x 3.5"
Raised Height: 6"

FEATURED LIGHTING



EL90DSP NEW

Patterned Facing

AC12V, 2.5W
Single-sided illumination
Dimensions: 1.6" x 3.5"
Raised Height: 6" / 12"
Customizable pattern face



EL90DDA NEW

Arch W / RGB

AC12V, 2.5W
Double-sided illumination
Dimensions: 1.6" x 3.5"
Raised Height: 12"

FEATURES & SPECIFICATIONS

- **Automatic Operation:**
Rises to full height at dusk and retracts at dawn automatically.
- **Damage Prevention:**
Safeguards against foot traffic, lawn equipment and other hazards.
- **12 VAC Compatible:**
Runs on standard 12 VAC landscape transformers — no new infrastructure needed.
- **Rugged & Weatherproof:**
IP66 rated. Fully sealed against dust and powerful water jets.
- **Modern Aesthetics:**
Sleek low-profile housing when retracted; clean lines when deployed.
- **Seamless Ambiance Control:**
Automates day/night transitions for consistent outdoor mood lighting.
- **High-Quality LEDs & Optics:**
Precision optical beams for controlled, targeted illumination.
- **Multiple CCT Options:**
Available in 2700K / 3000K / 4000K / 5000K.
- **Adjustable Illumination:**
Four-level brightness control for flexible scene management.
- **Variable Projection Angle:**
0–45° adjustable beam for uplighting (EL70U model).
- **Premium Construction:**
Durable aluminum housing with stainless-steel components.
- **Intellectual Property:**
Patented in Taiwan & China; patents pending in USA & Australia.

IP66 Waterproof

12 VAC

UL Listed

3/5-Yr Warranty