



- ✓ Premium Nichia Bin-sorted LEDs
- ✓ Top quality optical beams
- ✓ Universal Voltage
- ✓ Plug and play connectors
- ✓ Full Saturation to over 15 feet
- ✓ 5-Year Warranty

HB30 SERIES

ARCHITECTURAL LED LINEAR LIGHTING

HB308



Performance: 4.25w/ft | 359lm/ft
Beam Angles: 15°, 30°, 45°, 120°, 30°x60°
CCT: Static White
Control: Non-dimmable

HB3014



Performance: 4.5w/ft | 486lm/ft, 7.0w/ft | 700lm/ft
Beam Angles: 15°, 30°, 45°, 60°, 75°, 90°, 120°, 18°x26°, 30°x60°
CCT: Static Colors
Control: 0-10v dimming

HB3014R



Performance: 4.5w/ft | 356lm/ft, 7w/ft | 458lm/ft
Beam Angles: 120°
CCT: Static Colors
Control: 0-10v dimming

HB3014RH



Canopy or Wall Mounted

Performance: 4.5w/ft | 356lm/ft, 7w/ft | 458lm/ft
Beam Angles: 120°
CCT: Static Colors
Mount: Canopy/ceiling
Control: 0-10v dimming

HB3015



Performance: 6w/ft
Beam Angles: 15°, 20°, 30°, 45°, 60°, 75°, 90° 120°, 18°x26°, 30°x60°
CCT: RGB
Control: DMX

HB3016



Performance: 6w/ft
Optics: 15°, 20°, 30°, 45°, 60°, 75°, 90° 120°, 18°x26°, 30°x60°
CCT: RGBW
Control: DMX

MOUNTING OPTIONS



Black



Bronze



White



Silver

Stainless Adjustable or Flat brackets
Optional Louvers: 12", 24", 36" 48"
Optional Anodized Aluminum Extruded housing with Integral Glare Shield
Arm lengths: 6", 12", 18", 24" or 36"
Wall or Ground post mounting
Row mounted or stand-alone
Black, Bronze, White & Silver Powder-coated finish
*Additional RAL custom colors are available

COLOR TEMPERATURES



2700K 3000K 3500K 4000K 5000K 6500K



RGBW

CERTIFICATIONS

